



Product details:

- » Stops dirt and moisture at the door
- » High-twist nylon pile
- » Special colours going by Pantone, HKS or RAL possible for a surcharge
- » Special shapes possible
- » Skid resistant rubber back
- » PVC-free
- » Suitable for underfloor heating
- » 2 years guarantee
- » Made in Europe

Burning behaviour:

EN 13501-1 / CfI-s1

Total mat weight:

1.90 kg/sqm

Overall height:

approx. 7 mm

Dirt absorption:

470 g/sqm

Moisture absorption:

2 - 3 l/sqm

Application areas:

- » Indoor placement
- » Entrances
- » Corporate identity
- » Point of Sale
- » Any marketing message

Standard widths with borders: 60 cm, 75 cm, 85 cm, 115 cm, 150 cm and 200 cm

Standard widths without borders: 3 cm smaller than for mats with borders (e.g. 57 cm)

Standard lengths: all lengths up to 400 cm

Bespoke lengths: up to 700 cm

Colouration: Chromojet printing process

Pile: 100 % High-Twist Nylon (HTN) Polyamide 6.6

Pile height: approx. 6 mm

Pile weight: without substrate: 580 g/sqm

with substrate: 680 g/sqm

Backing: 100 % Nitrile rubber

Available with kleeled or smooth backing

Rubber thickness: 0.90 mm

Rubber weight: 1.20 kg/sqm

Border width: 10 mm

Available with or without borders

Border thickness: 1.90 mm

Cleaning: » Washable up to 60 °C

» Tumble dry up to 60 °C

Colours:

